

SUPERFAX

SUPERFAX PF-370



SPECIFICATIONS

SUPERFAX PF-370	
Paper sizes	Max: 297 (W) x 420 (L) mm / Min: 128 (W) x 182 (L) mm
Paper weight	45-135 gsm (145 gsm for Single fold)
Paper quality	Bond, Duplicating papers, Rough papers, Recycled papers
Fold types	For A3, A4, A5, Letter, Legal, Ledger sizes: 6 fold types are programmed (Single, Double Parallel, Fold out Letter, ZigZag, Gate) For the other sizes : Manual settings
Cross fold	Yes
Paper feeding system	Friction feed by 3 rubber rollers
Skew adjustment	Yes
Eject roller posi. Setting	Manual
Feed table capacity	500 sheets of 60gsm paper
Folding speed	2,400 to 7,200 sheets per hour for A4 Single fold
Counter	4-digit digital counter (addition) "0000-9999"
Total counter	Yes
Error detection	Jam map
Jam sensor	Yes
Paper empty detection	Yes
Paper eject sensor	Yes
Safety Interlock switch	Yes
Paper eject tray style	Neat stacking by carriage belt
Dimensions (In use)	920 (W) x 490 (D) x 525 (H) mm 790 (W) x 490 (D) x 525 (H) mm
Weight	32 kg
Power source	110/120 VAC or 220/240VAC, 50 or 60 Hz

Features

Automatic Settings – Six different folding types are programmed, each for International sizes A3/A4/A5 and the U.S sizes Letter/Legal/Ledger.

- ◆ Irregular and special sizes can be folded by manual set-up.
- ◆ Equipped with 4-digit addition counter.
- ◆ Diagnostic Display for visual observation to detect nature and the whereabouts of errors.
- ◆ 5 different folding speeds, slant correction device and miss-operation protection system.
- ◆ Equipped with conveyer belt output.
- ◆ Special paper feeding system as an option can also be used for coated and/or art papers for smooth feeding.