


SPECIFICATIONS

	PF-460	PF-440	PF-420
Paper Size	Max. 300mm x 432mm / Min. 91mm x 128mm (Single fold only)		
Paper Weight	46gsm to 160gsm * Up to 230gsm for single fold		
Paper Quality	Bond, HQ Duplication and Rough paper * Coated paper by use of special paper finder enclosed		
Fold Types	Single, Letter, Zig-zag, Double-parallel, Fold-out, Gate and Cross-fold		
Fold Position Setting	Automatic	Manual	
Feed Table Capacity	500 sheets of 64gsm paper		
Speed	3240-14400 sheets/h	8000 sheet/h (50Hz) 9000 sheet/h (60Hz)	
Counter	4-digit digital counter (addition or subtraction with auto-repeat)		
Number of Automatic fold types	36	N/A	
Storing fine adjustments	36	N/A	
Storing odd/special fold types	9	N/A	
Fold position setting by paper length	Yes	N/A	
Skew Adjustment	YES		
Paper feed pressure adjustment	5 levels of paper feed pressure and separator pressure adjustment	N/A	
Paper jam detection	Yes		
Error detection	Jam map and Error code	Jam map	
Paper empty detection	Yes		N/A
Detachable fold rollers	Yes		N/A
Automatic elevation of feed tray	Manual		
Positioning of eject roller	Manual		No eject roller
Paper ejection method	Neat stacking by carriage belt		Free fall
Dimensions (mm)	W870 x D530 x H520	W870 x D530 x H520	W820 x D530 x H520
Weight	33.5kg	33.5kg	27kg
Power consumption	75W		
Option	Perforation unit * Scoring Unit	N/A	Paper Guides for Cross-fold